

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织  
国际局



(43) 国际公布日:  
2005年4月28日 (28.04.2005)

PCT

(10) 国际公布号:  
WO 2005/038358 A1

(51) 国际分类号<sup>7</sup>: F25B 29/00

(21) 国际申请号: PCT/CN2004/000717

(22) 国际申请日: 2004年7月1日 (01.07.2004)

(25) 申请语言: 中文

(26) 公布语言: 中文

(30) 优先权:  
200310101604.7 2003年10月21日 (21.10.2003) CN

(71)(72) 发明人/申请人: 孙霆(SUN, Ting) [CN/CN]; 中国  
广东省珠海市前山福来花园10栋403号, Guangdong  
519070 (CN)。

(74) 代理人: 北京科龙寰宇知识产权代理有限公司  
(KELONG INTERNATIONAL INTELLECTUAL  
PROPERTY AGENT LTD.) 中国北京市海淀区北太  
平庄路25号北京豪威大厦315室, Beijing 100088  
(CN)。

(81) 指定国(除另有指明, 要求每一种可提供的国家保护):  
AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW,

BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM,  
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR,  
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,  
MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL,  
PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,  
ZM, ZW


(84) 指定国(除另有指明, 要求每一种可提供的地区保护):  
ARIPO(BW, GH, GM, KE, LS, MW, MZ, NA, SD,  
SL, SZ, TZ, UG, ZM, ZW), 欧亚专利(AM, AZ, BY,  
KG, KZ, MD, RU, TJ, TM), 欧洲专利(AT, BE, BG,  
CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,  
IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR),  
OAPI(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
ML, MR, NE, SN, TD, TG)

本国际公布:  
— 包括国际检索报告。

所引用双字母代码和其它缩写符号, 请参考刊登在每期  
PCT公报期刊起始的“代码及缩写符号简要说明”。

(54) Title: AIR HEAT PUMP TYPE HOT WATER STOVE

(54) 发明名称: 空气热能热泵式热水炉



(57) Abstract: This invention discloses an air heat pump type hot water stove, which includes a condenser, a throttling valve, an evaporator and a compressor connected successively. Plural condensers are connected with each other. First condenser forms by a water tank with a water joint and an outlet, and a built-in radiator. This invention has reduced the hot pollution for environment using heat pump principle to absorbing heat energy to burn hot water, and can offer refrigerating capacity while offering heat water, and saving energy greatly. Plural condensers are connected in series or other connecting way, which can get the hot water of different temperature, from 45°C to 100°C, to satisfy different demand. Two kinds of evaporators can offer cold quantity directly or indirectly. The condenser group with an individual housing can get hot water alone with other existing air-conditioner connected therewith.

[见续页]